



(AM) Acousto-Magnetic

LABEL DEACTIVATOR

AM Label Deactivator is an essential accessory required with any AM EAS system where label protection is desired.

AMERSEC® AM STANDARD Deactivator is designed for stores which demand fast and reliable deactivation and advanced Next Generation features such as remote maintenance and StoreMonitor - the AMERSEC® online data management solution.

The AM Deactivator is equipped with a key lock for controlled access. It is a smart device that can provide a full overview of deactivation activities. With these features retailers have complete control over the deactivation behavior in a secured store.

AMERSEC® AM Deactivator can also be integrated with a scanner or a self-operated POS.

FEATURES:

- StoreMonitor data management
- Remote tuning/maintenance
- Event management
- Air synchronization
- Status and deactivation LED indicators
- Connectivity with cashpoint scanners
- Deactivation range up to 12 cm
- Flat pads
- Key lock
- Deactivation sound check
- Compatibility with all AM systems
- Energy saving mode

TECHNICAL SPECS:

- Voltage: 220 V
- Operating frequency: 58 kHz
- Sweep frequency: 57.8 - 58.2 kHz
- Repetition rate: 5 Hz
- Consumption detection: 3 W
- Consumption deactivation: 0 W
- Operating temperature: 0-50 °C

AM STANDARD DEACTIVATOR



The new functional design of the Deactivator consists of 3 LED status indicators as well as a lockable power switch. For service maintenance the unit can be connected to a local PC or laptop. An online connection then enables technical support to provide all adjustment services immediately.

UNIT DIMENSIONS	WEIGHT	KEY LOCK	SOUND INDICATION	ONLINE CONNECTION
185x170x51 mm	0.51 kg	✓	✓	✓

DESK-TOP PAD



Designed for stores where the deactivation pad must be placed on top of the cash desk. The cable output of the

DESK-TOP PAD is placed on its side and therefore can be easily covered in an attractive way without the need to drill or cut the cash desk.

UNIT DIMENSIONS	HOLE SIZE	DISTANCE FROM DEACTIVATOR
160x160x22 mm	-	up to 2 m

DESK-INSERTABLE PAD



Designed to fit into a custom-cut hole in a cash desk to achieve a flush fit with the till area. A major part of the pad is hidden and does not disturb the design of the cash desk.

UNIT DIMENSIONS	HOLE SIZE	DISTANCE FROM DEACTIVATOR
190x190x15 mm	165x165 mm	up to 2 m

SENSO PAD



Designed to replace installations of old and/or non-functioning deactivators. The pad has exactly the same dimensions as one of the most widespread AM label deactivators on the market, thus fixing a new deactivator is easy and requires no changes to the client's furnishings.

UNIT DIMENSIONS	HOLE SIZE	DISTANCE FROM DEACTIVATOR
430x211x15 mm	175x210 mm	up to 2 m



(RF) Radio-Frequency LABEL DEACTIVATOR

RF Label Deactivator is an important part of every installation where merchandize is secured with RF soft labels. AMERSEC® offers a choice of two different versions each designed for various end users and different needs.

AMERSEC® RF STANDARD Deactivator can be enabled with an online connection for remote maintenance and StoreMonitor - the AMERSEC® online data management solution.

The RF STANDARD Deactivator is equipped with a key lock for controlled access. It is a smart device that can provide a full overview of deactivation activities. With these features retailers have complete control over the deactivation behavior in a secured store.

AMERSEC® RF MINI Deactivator gives you the advantage of cost-effectiveness without the possibilities of advanced features.

AMERSEC® RF Deactivators can also be integrated with a scanner or a self-operated POS.

FEATURES:

- StoreMonitor data management
- Remote tuning/maintenance
- Event management
- Air synchronization
- Status and deactivation LED indicators
- Connectivity with cashpoint scanners
- Deactivation range 15 - 30 cm
- Special protective mode with zero level interference with any system on the market
- Key lock
- Deactivation sound check
- Compatibility with all RF systems
- Energy saving mode

TECHNICAL SPECS:

- Voltage: 15V AC
- Operating frequency: 8.2 MHz
9.5 MHz
10.5 MHz
- Sweep frequency: +- 600 kHz
- Consumption: max 5 W
- Operating temperature: 0-50 °C

RF STANDARD DEACTIVATOR



The new functional design of the deactivator consists of 3 LED status indicators as well as a lockable power switch. For service maintenance the unit can be connected to a local PC or laptop. An online connection then enables technical support to provide all adjustment services immediately.

UNIT DIMENSIONS	WEIGHT	KEY LOCK	SOUND INDICATION	ONLINE CONNECTION
185x170x51 mm	0.51 kg	✓	✓	✓

RF MINI DEACTIVATOR



AMERSEC® RF MINI DEACTIVATOR is a simple and system friendly device which is easy to install. It offers basic settings including wireless synchronization option. It is a low power consumption product.

UNIT DIMENSIONS	WEIGHT	KEY LOCK	SOUND INDICATION	ONLINE CONNECTION
95x85x28 mm	0.16 kg	✗	✗	✗

RUBBER PAD



Standard black rubber pad which is ideal for food stores or other stores where a desk-top rubber pad is desired.

DIMENSIONS	DISTANCE FROM DEACTIVATOR
298x250x8 mm	up to 2 m

BASIC PAD



Standard black plastic pad for desk-top mounting.

DIMENSIONS	DISTANCE FROM DEACTIVATOR
245x245x4 mm	up to 2 m

WAND PAD



Hand-held pad for a more mobile deactivation solution.

DIMENSIONS	DISTANCE FROM DEACTIVATOR
300x100x8 mm	up to 2 m