

Product Data Sheet

KZ715I

Kilsen KL700A Series Addressable Fire Detector Base with Isolator

General

The KZ715I is a detector base with built-in isolator for use with Kilsen KL700A addressable detectors. The built-in dual isolator protects the loop from short circuit conditions on either side of the base. An LED on the side of the KZ715I indicates the isolation status of base.

Series overview

The KZ715I is part of the KZ705 series, 5 contact base family. The KZ705 series bases consist of components that may be used with both addressable KL700A as well as conventional KL700 detectors. The KZ715I is specific for use with Kilsen KL700A addressable systems.

The range cosists of:

- a standard base (KZ705)
- a relay base (KZ705R)
- a sounder base (KZ715AS)
- an isolator base (KZ715I)
- a deep base (KZD705)

Installation options

The KZ715I, as with all KZ705 series bases, support the connection of a remote indicator. It allow for both surface mount installations with rear cable entry, as well as direct side cable entry. Should conduit entry into the base be required, the KZ715I can accommodate when used with the optional S700 base accessory.



Standard Features

- Built-in dual isolator
- Universal base for addressable detectors
- Cable screen/earth terminal support
- Remote alarm indicator support
- Rear and side cable entry support

KZ715I

Kilsen KL700A Series Addressable Fire Detector Base with Isolator

Specifications

| Dimensions (Ø x h) | 100 x 29 mm |
|------------------------------------|----------------|
| Weight | 49 g |
| Operating voltage | 18.5 to 39 VDC |
| Current specifications | 50 μA |
| Quiescent | < 240 µA |
| Isolated | < 7 mA |
| Max. capacity | 800 mA |
| Line resistance | < 0.1 Ohm |
| Environmental characteristics | |
| Operating temperature | -10°C to +55°C |
| Storage temperature | -10°C to +70°C |
| Relative humidity (non-condencing) | 10 to 95% |
| IP Rating | IP30 |
| Colour | White |

Ordering Information

| Part No. | Description |
|----------|---|
| KZ715I | Kilsen KL700A Series Addressable Fire Detector Base with Isolator |
| PA25/3L | Low current remote LED indicator |
| S700 | Surface Mount Accessory for KZ700 and KZ705 Series Bases |

